


Automated Laser Linewidth and Phase/Frequency Noise Measurement System




OEwaves' Ultra-Narrow Laser Linewidth and Frequency Noise Measurement System utilizes a homodyne methodology for automated measurement capable of testing ultra-low phase noise laser sources. The user friendly test system is capable of rapidly measuring <10 Hz of Lorentzian linewidth of a laser source without the complicated setup typically required to make such a narrow linewidth measurement. This homodyne based system is unique in wide band measurement without requiring another low noise reference laser source. The complete system operates with ease, speed and precision, and a simple graphic user interface via a PC, without requiring any additional test equipment. The unmatched ultra-low phase/frequency noise measurement system is scalable to various input wavelengths and capable of low relative intensity noise (RIN) measurement.

Features

- Ultra-Narrow/Low Linewidth/ Frequency Noise Measurement
- Fast Real-Time Measurement
- Fully Automated
- No Low Noise Reference Source Required
- User Friendly Interface
- Simple PC-based Operation
- 3U x 19" Rack System
- Customizable Configurations, Upgrades, and Options

Optional Configurations

- Extended input wavelength range measurements of 760nm-2.2 um
- RIN Measurements
- Extended Input Power Range
- Performance Level and Frequency Range Options and Upgrades



Typical Frequency Noise Measurement Sensitivity At 1.5 Microns

Graphic User Interface



Specifications

Parameter	1530-1565nm Input			
Frequency Noise Sensitivity	10 Hz	100 Hz	1 kHz	>10kHz
	50 Hz/√Hz	10 Hz/√Hz	2 Hz/√Hz	1 Hz/√Hz
Offset Frequency Range	10Hz - 1MHz			
Lorentzian Linewidth Sensitivity	<10 Hz			
Optical Input Power Range	+5 to +15 dBm			
Measurement Types	Homodyne RIN option			
Display Functions	Spectrum Spectral Density Markers Spurious Content			
Data Storage & I/O	HDD USB Port			
Resolution Bandwidth	0.1 Hz - 200 kHz			
Operating Temperature Range	15° - 35° C			
Power	110/120 or 220/240 Vac, 50/60 Hz			
Size	3U x 19" Rack Mount			
Options				
Extended Input Power	0 to +20 dBm (Consult Factory)			
Custom Optical Input Wavelength Range	Example: 1950-2050 nm (Consult Factory)			
Extended Offset Frequency Range	1 Hz - 10 MHz or 100 MHz			
Additional Measurement	Relative Intensity Noise (RIN)			

For ordering or other inquiries contact:



465 N. Halstead Street, Suite 140 • P 626 351 4200
Pasadena, California 91107 USA • E sales@oewaves.com

NOTE: These specifications are subject to change without notice due to OEwaves ongoing development cycle. Unless otherwise noted, all specifications in this documents are to be treated as "typical," actual performance may vary contingent on operating environment. Patents Pending.